


DYNA FLEX

SAE 100R8

8110 (ORANGE) NON-CONDUCTIVE



Recommended For: Medium pressure hydraulic and pneumatic systems.
Meets or exceeds SAE 100R8 requirements.

Inner Core: Oil resistant seamless thermoplastic elastomer tube.

Reinforcement: Braided high tensile aramid fiber.

Cover: Orange high abrasion resistant polyurethane.

Temperature Range: -40 degrees F. to +212 degrees F.
(-40 degrees C. to +100 degrees C.)

Hose Part No.	Nominal I.D.		Nominal O.D.		Maximum Oper. Press.		Minimum Burst Press.		Min. Bend Radius (In.)	Wt. Per 100 Ft. (Lbs.)
	In.	mm.	In.	mm.	PSI	Bar	PSI	Bar		
8110-03	3/16	4.76	.405	10.29	5,000	345	20,000	1,379	3/4	5.5
8110-04	1/4	6.35	.485	12.30	5,000	345	20,000	1,379	1-1/4	6.6
8110-06	3/8	9.53	.645	16.38	4,000	276	16,000	1,103	2	10.5
8110A-08	1/2	12.70	.760	19.30	3,500	241	14,000	965	3	12.3
8110-2P-12	3/4	19.0	1.18	30.10	2,250	155	9,000	621	5	30