

SWRG-2P-08 (GREEN)



Recommended For: Use on high pressure sewer cleaning and jetting equipment.

Innercore: Seamless polyester tube

Reinforcement: Two braids of high tensile synthetic fiber

Cover: Green high abrasion resistant polyurethane

Temperature Range: -40 degrees F. to +122 degrees F.
(-40 degrees C. to +50 degrees C.)

Hose Part No.	Nominal I.D.		Nominal O.D.		Maximum Oper. Press.		Minimum Burst Press.		Min. Bend Radius (In.)	Wgt. Per 100 Ft. (Lbs.)
	In.	mm.	In.	mm.	PSI	BAR	PSI	BAR		
SWRG-02	1/8	3.18	.305	7.75	4000	276	10000	689	1/2	2.5
SWRG-03	3/16	4.76	.405	10.29	4000	276	10000	689	3/4	5.5
SWRG-04	1/4	6.35	.505	12.83	4000	276	10000	689	1-1/4	7.0
SWRG-2P-06	3/8	9.53	.645	16.38	4000	276	10000	689	2	10.5
SWRG-2P-08	1/2	12.70	.81	20.57	4000	276	10000	689	3	15.0

DYNA FLEX, INC.
7300 INDUSTRIAL PARK BLVD.
MENTOR, OHIO 44060 U.S.A.

PHONE: (440) 946-0719 TOLL FREE: (800) 525-8463 FAX: (440) 946-4620
Web Site: www.dynaflexinc.com E-Mail: sales@flexinc.com