

7102 (HI NU-BLUE TWO) ®



Recommended For: Use in Airless/Wireless paint spray applications

Innercore: Nylon (Flexible)

Reinforcement: Two braids high tensile conductive synthetic fiber

Cover: Blue high abrasion resistant polyurethane

Temperature Range: -65 degrees F. to +212 degrees F.
(-54 degrees C. to +100 degrees C.)

Hose Part No.	Nominal I.D.		Nominal O.D.		Maximum Oper. Press.		Min. Bend Radius (In.)	Wgt. Per 100 Ft. (Lbs.)
	In.	mm.	In.	mm.	PSI	BAR		
7102-03	3/16	4.76	.405	10.29	3,300	227	3/4	5.5
7102-04	1/4	6.35	.505	12.83	3,300	227	1-1/4	7.0
7102-06	3/8	9.53	.645	16.38	3,300	227	2	10.5
7102-08	1/2	12.70	.810	20.57	2,000	138	3	15.0

NOTE: Paint spray hose is furnished only as a completed assembly. Hose will be coiled and cut to length specified by customer. All hose assemblies come complete with hose ends, spring guards and "Warning Tags".

NOT TO BE USED WITH PUMPS OR EQUIPMENT THAT EXCEED THE MAXIMUM OPERATING PRESSURE.