

DYNA FLEX INC.

**SEWER CLEANING
SWROE (ORANGE)**



Recommended For: Use on high pressure sewer cleaning equipment.

Innercore: Orange seamless polyolefin tube

Reinforcement: Two braids high tensile synthetic fiber

Cover: Bonded high abrasion resistant orange polyether-urethane featuring a snag resistant slicker surface.

Temperature Range: -40 degrees F. to +122 degrees F.
(-40 degrees C. to +50 degrees C.)

Hose Part No.	Nominal I.D.		Nominal O.D.		Maximum Oper. Press.		Minimum Burst Press.		Min. Bend Radius (In.)	Wgt. Per 100 Ft. (Lbs.)
	In.	mm.	In.	mm.	PSI	BAR	PSI	BAR		
SWROE-12	3/4	19.1	1.18	29.85	2,500	172	6,250	431	5	29.0
SWROE-16	1	25.4	1.43	36.32	2,500	172	6,250	431	6	40.0
SWROE-20	1-1/4	31.8	1.77	44.96	2,500	172	6,250	431	8	60.0

**DYNA FLEX, INC.
7300 INDUSTRIAL PARK BLVD.
MENTOR, OHIO 44060 U.S.A.**

PHONE: (440) 946-0719 TOLL FREE: (800) 525-8463 FAX: (440) 946-4620
Web Site: www.dynaflexinc.com E-Mail: sales@flexinc.com