

SWRB (BLACK)



Recommended For: Use on high pressure sewer cleaning and jetting equipment.

Innercore: Seamless polyester elastomer tube

Reinforcement: Braided high tensile aramid fiber

Cover: Black high abrasion resistant polyurethane

Temperature Range: -40 degrees F. to +122 degrees F.
(-40 degrees C. to +50 degrees C.)

Hose Part No.	Nominal I.D.		Nominal O.D.		Maximum Oper. Press.		Minimum Burst Press.		Min. Bend Radius (In.)	Wgt. Per 100 Ft. (Lbs.)
	In.	mm.	In.	mm.	PSI	BAR	PSI	BAR		
SWRB-03	3/16	4.76	.390	9.91	5,000	345	20,000	1397	3/4	5.5
SWRB-04	1/4	6.35	.480	12.19	5,000	345	20,000	1379	1-1/4	7.0
SWRB-06	3/8	9.53	.645	16.38	4,000	276	16,000	1103	2	10.5
SWRB-08	1/2	12.70	.810	20.57	4,000	241	14,000	965	3	15.0

DYNA FLEX, INC.
7300 INDUSTRIAL PARK BLVD.
MENTOR, OHIO 44060 U.S.A.

PHONE: (440) 946-0719 TOLL FREE: (800) 525-8463 FAX: (440) 946-4620
Web Site: www.dynaflexinc.com E-Mail: sales@flexinc.com