

## **7100 (NU-BLU) ®**



**Recommended For:** Use in Airless/Wireless paint spray applications

**Innercore:** Nylon (Flexible)

**Reinforcement:** Braided high tensile conductive synthetic fiber

**Cover:** Blue high abrasion resistant polyurethane

**Temperature Range:** -65 degrees F. to +212 degrees F.  
(-54 degrees C. to +100 degrees C.)

Hose Part No.	Nominal I.D.		Nominal O.D.		Maximum Oper. Press.		Min. Bend Radius (In.)	Wgt. Per 100 Ft. (Lbs.)
	In.	mm.	In.	mm.	PSI	BAR		
7100-03	3/16	4.76	.405	10.29	3,300	227	3/4	5.5
7100-04	1/4	6.35	.505	12.83	3,300	227	1-1/4	7.0
7100-06	3/8	9.53	.645	16.38	3,300	227	2	10.5
7100-08	1/2	12.70	.810	20.57	2,000	138	3	15.0

NOTE: Paint spray hose is furnished only as a completed assembly. Hose will be coiled and cut to length specified by customer. All hose assemblies come complete with hose ends, spring guards and "Warning Tags".

***NOT TO BE USED WITH PUMPS OR EQUIPMENT THAT EXCEED THE MAXIMUM OPERATING PRESSURE.***