

# ***DYNA FLEX***

# PAINT SPRAY

## **8100 (SUPR-NU SPRAY) ®**



**Recommended For:** Use in Airless/Wireless paint spray applications. Lighter than comparable wire reinforced paint spray hoses.

**Innercore:** Nylon (Flexible)

**Reinforcement:** Braided high tensile conductive aramid fiber

**Cover:** Red high abrasion resistant polyurethane

**Temperature Range:** -65 degrees F. to +212 degrees F.  
(-54 degrees C. to +100 degrees C.)

Hose Part No.	Nominal I.D.		Nominal O.D.		Maximum Oper. Press.		Min. Bend Radius (In.)	Wgt. Per 100 Ft. (Lbs.)
	In.	mm.	In.	mm.	PSI	BAR		
8100-03	3/16	4.76	.390	9.19	6,000	413	3/4	5.5
8100-04	1/4	6.35	.480	12.19	6,000	413	1-1/4	7.0
8100-06	3/8	9.53	.645	16.38	5,000	345	2	10.5
8100-08	1/2	12.70	.810	20.57	3,500	241	3	15.0

NOTE: Paint spray hose is furnished only as a completed assembly. Hose will be coiled and cut to length specified by customer. All hose assemblies come complete with hose ends, spring guards and "Warning Tags".

***NOT TO BE USED WITH PUMPS OR EQUIPMENT THAT EXCEED THE MAXIMUM OPERATING PRESSURE.***

***DYNA FLEX, INC.  
7300 INDUSTRIAL PARK BLVD.  
MENTOR, OHIO 44060 U.S.A.***

PHONE: (440) 946-0719 TOLL FREE: (800) 525-8463 FAX: (440) 946-4620  
Web Site: [www.dynaflexinc.com](http://www.dynaflexinc.com) E-Mail: [sales@flexinc.com](mailto:sales@flexinc.com)