

DYNA FLEX

SAE100R7 & SAE100R8

(ORANGE) TWIN-LINE DIVER HOSE



Recommended For: Medium pressure hydraulic systems. Twin-line consists of a 1 inch SAE 100R7 hose fused with a 3/4 inch SAE 100R8 hose.

Inner Core: Oil resistant synthetic polyester tubes

Reinforcement: Each hose has two braids of high tensile synthetic fiber

Cover: Bonded orange non-conductive high abrasion resistant polyurethane mold and fungus resistant polyether-urethane, featuring an anti-stick additive for a snag resistant slick surface.

Temperature Range: -40 degrees F. to + 212 degrees F.
(-40 degrees C. to +100 degrees C.)

Hose Part No.	Nominal I.D.		Nominal O.D.		Maximum Oper. Press.		Minimum Burst Press.		Min. Bend Radius (In.)	Wt. Per 100 Ft. (Lbs.)
	In.	mm.	In.	mm.	PSI	Mpa	PSI	Mpa		
8110-2P-12/7110-16T (consisting of 1 each below)										
8110-2P-12	3/4	19.05	1.185	30.10	2,250	15.5	9,000	62	6	65
7110-16	1	25.4	1.42	36.07	1,000	6.9	4,000	27.6		

DYNA FLEX, INC.
7300 INDUSTRIAL PARK BLVD.
MENTOR, OHIO 44060 U.S.A.

PHONE: (440) 946-0719 TOLL FREE: (800) 525-8463 FAX: (440) 946-4620
Web Site: www.dynaflexinc.com E-Mail: sales@flexinc.com Rev C, April 23, 2013