

# **DYNA FLEX**

## **SEWER JETTING**

**SWRR (RED) 5,000 PSI**



**Recommended For:** Use on high pressure sewer jetting equipment.

**Inner Core:** Neutral color seamless polyester tube

**Reinforcement:** Two braids of high tensile synthetic fiber

**Cover:** Bonded red high abrasion mold and fungus resistant polyether-urethane, featuring an anti-stick additive for a snag resistant slick surface.

**Temperature Range:** -40 degrees F. to +122 degrees F.  
(-40 degrees C. to +50 degrees C.)

Hose Part No.	Nominal I.D.		Nominal O.D.		Maximum Oper. Press.		Minimum Burst Press.		Min. Bend Radius (In.)	Wt. Per 100 Ft. (Lbs.)
	In.	mm.	In.	mm.	PSI	Mpa	PSI	Mpa		
SWRR-03	3/16	4.8	.41	10.29	5,000	34.5	12,500	86.2	1.7	5
SWRR-04	1/4	6.4	.51	12.83	5,000	34.5	12,500	86.2	2	7
SWRR-06	3/8	9.53	.65	16.51	5,000	34.5	12,500	86.2	2-1/2	11
SWRR-08	1/2	12.7	.76	19.3	5,000	34.5	12,500	86.2	3	12.3

**DYNA FLEX, INC.**  
**7300 INDUSTRIAL PARK BLVD.**  
**MENTOR, OHIO 44060 U.S.A.**

PHONE: (440) 946-0719 TOLL FREE: (800) 525-8463 FAX: (440) 946-4620  
Web Site: [www.dynaflexinc.com](http://www.dynaflexinc.com) E-mail: [sales@flexinc.com](mailto:sales@flexinc.com) Rev C, April 23, 2013